



Technical Data Sheet



AquaStop™ Waterproof compound

Product

AquaStop™ allows you to waterproof concrete surfaces, prior to tiling, shower bases, bathrooms, kitchens, and laundry rooms, where any floor tiles are laid. Also great for retaining walls and balconies.

Benefits

► Provides waterproof barrier against rising dampness

Surface preparation

All surfaces must be clean and free from all foreign matter, grease, fungus sealers, dust loose toppings etc. A cleaned surface will maximise bond. To remove build up of surface matters use a high pressure washer. If concrete has been Sealed, use Sealer Strippa to remove the sealer, follow Sealer Strippa guidelines.

To remove grease and oil stains: wet area with hot water then apply Cleanall scrub with a broom on and around area for a min of 5 minutes, keep moist at all times, DO NOT allow to dry, then rinse off. Repeat if necessary.

To remove tyre marks: use Markz off™ as per application guidelines.

To remove moss or fungus: dilute bleach 1 to 10 parts water in a watering can, apply over the surface and allow to penetrate for a minimum of 2 hours. Rinse off using a high pressure water blast, repeat if necessary. Walls usually require only a pressure wash. Cement sheet bases must be clean before applying prime coat, cracks or depressions must be repaired. This can be achieved by using an amount of the base coat mix.

Prime Coat

Mix approximately 2 parts water to 1 part Allbond®. Prime the area to be treated with this mixture using a broom or roller.

Mixture preparation

Add approximately 2.5 / 3 litres of water to 10kg Aquastop™, stir thoroughly to a batter like consistency.

Application

Prior to application it is advisable to protect walls and structures to avoid risk of possible stain.

Cut in and around walls and steps first with the mixture. Then apply thoroughly mixed mixture to the surface using a broom or trowel, ensuring full and even coverage to approximately 1.6mm thick.

Equipment

Trowel, Broom, Drill, Stirrer, all to be washed frequently with water

Coverage

Approximately 8 sq mtrs per 10kg pail

Package

10kg pail

Shelf life

Approximately 18 months, providing stored correctly and un opened

Storage

Store in a well protected dry area

Handling

Avoid contact with skin and eyes, wear gloves and eye protection

Properties

Appearance: Grey powder
Solubility in water: Insoluble

Disclaimer: Warranty and Limitation of liability:

Bescon warrants its products to be free from faults/defects in material and workmanship. Bescon's sole obligation and Buyer's exclusive remedy in connection with the products shall be limited, at Bescon's option, to either replacement of products not conforming to this Warranty or credit to Buyer's account of the invoiced amount of the nonconforming product/s. Any claim under this Warranty must be made by the Buyer to Bescon in writing within five (5) days of Buyer's discovery of the claimed defect, but in no event later than the expiration of the applicable shelf life, or one year from the delivery date, whichever is earlier. Buyer's failure to notify Bescon of such non-conformance as required herein shall bar Buyer from recovery under this warranty. Bescon makes no other warranties concerning the product. No other warranties, whether express, implied or statutory, such as warranties of merchantability or fitness for a particular purpose shall apply. In no event shall Bescon be liable for consequential or incidental damages. Any recommendation or suggestion relating to the use of the products made by Bescon, whether in its Technical Data literature, or in response to specific inquiry or otherwise, is based on data believed to be reliable; however, the products and information are intended for use by Buyers having requisite skill and know-how in the industry, and therefore it is for Buyer to satisfy themselves of the suitability of the products for their own particular use and it shall be deemed that the Buyer has done so, at their sole discretion and risk. Variation in environment, changes in procedures of use, or extrapolation of data may cause unsatisfactory results.

Limitation of Liability:

Bescon's liability on any claim of any kind, including claims based upon Bescon's negligence or strict liability, for any loss or damage arising out of connected with, or resulting from the use of the products, shall in no case exceed the purchase price of the products or part thereof which gives rise to the claim. In no event shall Bescon be liable for consequential or incidental damages.