



Technical Data Sheet



StaSeal® ST Spraytex™ concrete resurfacing sealer *previously known as StaSeal® KC*

Product	StaSeal® ST is a single pack two coat system acrylic base solution. Designed to cure and seal Spraytex™ Concrete resurfacing
Benefits	<ul style="list-style-type: none">▶ Reduces efflorescence▶ Protects against fading and powdering▶ Minimises softening of new Spraytex™ Concrete resurfacing▶ Improves durability
Surface preparation	<p>New Spraytex™ surfaces: requires no special preparation, prior to sealing provided the surface is clean and dry. Immediate same day sealing of the new surface will reduce the possibility of efflorescence.</p> <p>Existing Spraytex™ surfaces: previously sealed surfaces should be clean, and free from all foreign matters, before resealing to ensure adhesion.</p> <p>To remove grease and oil stains: wet area with hot water then apply Cleanall scrub with a broom on and around area for a min of 5 minutes keeping moist at all times, DO NOT allow to dry, then rinse off. Repeat if necessary.</p> <p>To remove moss or fungus: dilute bleach 1 to 10 parts water in a watering can, apply over the surface and allow to penetrate for a minimum of 2 hours. Rinse off using a high pressure water blast, repeat if necessary.</p> <p>To remove tyre marks: use Markz off™ as per application guidelines.</p>
Sealer application	New and Existing: Apply first and second coat undiluted, evenly without pooling. Allow min 2 hours between coats.
Precautions	<p>Sealing steep and sloping surfaces: is not recommended, as it reduces pedestrian and vehicle safety and can be very slippery in wet or dry conditions.</p> <p>Sealing in summer: the addition of 2 litres Solulene® in the final coat will help reduce blistering. Sealing early in the morning or late in the day is not recommended, due to early morning dew and night condensation. Sealer affected by moisture will lose gloss, adhesion properties and could have a white blooming appearance.</p>
Curing	Full curing is not achieved for up to 7 days. Avoid parking cars on new sealed surfaces until full curing is achieved. Foot traffic following day.
Coverage	Approximately 5 sq mtrs per litre
Equipment	Airless Spray, Sealer Broom, Dacron Roller, or Lambs Wool Applicator, all to be cleaned with Solulene®
Package	20 lt pail, available in Clear
Shelf life	Approximately 18 months, providing stored correctly and unopened
Storage	Store in a well protected cool place, well ventilated and away from excessive heat. Keep away from all ignition sources
Handling	Avoid contact with skin and eyes, wear gloves and eye protection. Avoid breathing vapours, wear respiratory mask
Properties	Appearance: Pale Clear liquid Odour: Turps like Solubility in water: Insoluble Flammability: Flammable

Disclaimer: Warranty and Limitation of liability:

Bescon warrants its products to be free from faults/defects in material and workmanship. Bescon's sole obligation and Buyer's exclusive remedy in connection with the products shall be limited, at Bescon's option, to either replacement of products not conforming to this Warranty or credit to Buyer's account of the invoiced amount of the nonconforming product/s. Any claim under this Warranty must be made by the Buyer to Bescon in writing within five (5) days of Buyer's discovery of the claimed defect, but in no event later than the expiration of the applicable shelf life, or one year from the delivery date, whichever is earlier. Buyer's failure to notify Bescon of such non-conformance as required herein shall bar Buyer from recovery under this warranty. Bescon makes no other warranties concerning the product. No other warranties, whether express, implied or statutory, such as warranties of merchantability or fitness for a particular purpose shall apply. In no event shall Bescon be liable for consequential or incidental damages. Any recommendation or suggestion relating to the use of the products made by Bescon, whether in its Technical Data literature, or in response to specific inquiry or otherwise, is based on data believed to be reliable; however, the products and information are intended for use by Buyers having requisite skill and know-how in the industry, and therefore it is for Buyer to satisfy themselves of the suitability of the products for their own particular use and it shall be deemed that the Buyer has done so, at their sole discretion and risk. Variation in environment, changes in procedures of use, or extrapolation of data may cause unsatisfactory results.

Limitation of Liability:

Bescon's liability on any claim of any kind, including claims based upon Bescon's negligence or strict liability, for any loss or damage arising out of or connected with, or resulting from the use of the products, shall in no case exceed the purchase price of the products or part thereof which gives rise to the claim. In no event shall Bescon be liable for consequential or incidental damages.